

# **Technical Data Sheet**

Page No. 1

#### 1. Product and Introduction

Product Name	P395
Backing Material	Polyester Y wt
Bonding	Resin over Resin
Mineral Type	Aluminum Oxide (Compact Grain)
Coating State	Closed Coat
Manufacturing Width	1360mm

#### 2. Available Grit

Grit	16	24	36	40	50	60	80	100	120	150	180	220
						$\triangle$	$\triangle$		$\triangle$		$\triangle$	
	240	280	320	360	400	500	600	800	1000	1200	1500	2000
	Δ		Δ		Δ		Δ					

<sup>■</sup> Rough(Grinding)

Finishing(Polishing) ▶

# 3. Advantage

- ◆ Excellent Long life.
- ◆ High productivity.
- ◆ Providing uniform scratch pattern.

#### 4. Operation / Application

- ♦ Stainless steel sheets & coils.
- ♦ Automotive.
- ♦ Welding seams containers.

- ◆ Wet or Dry sanding
- ◆ Turbine blade.

### 5. Work pieces

◆ Steel(alloyed, non-alloyed).

♦ Stainless Steel

◆ Non-ferrous metals.

# 6. Available Sander / Grinder

Centerless.

◆ Backstand.

♦ Disc.

◆ Wide & Narrow belt.

◆ Conveyorized through feed belt grinder.

628-4, Seonggok-dong, Ansan, Gyeonggi-do, Korea www.sunmight.com

<sup>-</sup> Introductory Remarks ●: Standard Grit △: Non Standard Grit