

# **Technical Data Sheet**

Page No. 1

#### 1. Product and Introduction

Product Name	P963
Backing Material	Polyester Xwt.
Bonding	Resin over Resin
Mineral Type	Ceramic grain
Coating State	Closed coat
Manufacturing Width	1320mm

## 2. Available Grit

Grit	16	24	36	40	50	60	80	100	120	150	180	220
			$\triangle$	•	$\triangle$	•	•	•	•			
	240	280	320	360	400	500	600	800	1000	1200	1500	2000

<sup>■</sup> Rough(Grinding)

Finishing (Polishing) ▶

### 3. Advantage

- ♦ High cutting performance. (Ceramic grain)
- ♦ Active filler reduce heat build up, so there's less burning parts.
- ◆ New cutting edges (Self-sharpening) make easy grinding.
- ◆ Moderate pressure applications.

#### 4. Operation / Application

- ◆ Dry or Wet Grinding.
- ◆ Heat-sensitive alloys.
- ♦ Belt, Discs.

#### 5. Work pieces

- ♦ Stainless steel & Carbon steel.
- ◆ Nickel and Cobalt alloy.
- ♦ Titanium.

#### 6. Available Sander / Grinder

♦ Wide & Narrow Belt Grinder.

Disc Sander

<sup>-</sup> Introductory Remarks ●: Standard Grit △: Non Standard Grit



# **Technical Data Sheet**

Page No. 2

♦ Back stand sander.