

# **Technical Data Sheet**

Page No. 1

#### 1. Product and Introduction

Product Name	R330					
Backing Material	Poly/Cotton 65/35, J-Flex					
Bonding	Resin over Resin					
Mineral Type	Premium Aluminum Oxide					
Coating State	Closed coat					
Manufacturing Width	1320mm					

#### 2. Available Grit

Grit	16	24	36	40	50	60	80	100	120	150	180	220
						•	•	•	•	•	•	•
	240	280	320	360	400	500	600	800	1000	1200	1500	2000
	•		•		•		Δ					

<sup>■</sup> Rough(Grinding)

Finishing(Polishing) ▶

### 3. Advantage

- ◆ Suitable for contour and mould part sanding(Highly flexible backing)
- ♦ Better Finishing
- ◆ Cool Grinding

## 4. Operation / Application

- ◆ Dry or Wet Sanding.
- ◆ Deburring of steel and stainless steel
- ♦ Back stand

#### 5. Work pieces

- ◆ Stainless steel(cutlery) & Carbon steel
- ♦ Nickel alloy
- ◆ Surgical instruments

#### 6. Available Sander / Grinder

- ◆ Narrow belt sander
- Back stand sander

628-4, Seonggok-dong, Ansan, Gyeonggi-do, Korea www.sunmight.com

<sup>-</sup> Introductory Remarks ●: Standard Grit △: Non Standard Grit